



**ONE-STOP ALARM SOLUTION
FOR MORE THAN 15 YEARS!**

Contact us by:

Company name:
SHENZHEN SUMRING TECHNOLOGY CO., LTD
Address:
C-510, Guobao Security Building, No. 129 Pingxinbei Road,
Pinghu Street, Longgang District, Shenzhen City, Guangdong,
China
Telephone: 0086 755 89571625
Email: info@sumring.com
Youtube: @sumringeffie5250
Facebook: @alarm.sumring

SHENZHEN SUMRING TECHNOLOGY CO., LTD



COMPANY PROFILE

OEM FOR WELL KNOWN BRAND

Shenzhen SUMRING technology Co., Ltd is a complete alarm solution supplier. Products cover Detector, fire alarm system and security accessories;

Standardized management

SUMRING implement the ISO 9001 standard management, continuously follows the trend of global advanced fire alarm development, invest 20% of earnings into research & development every year and releases 2 new products in 6 months. To Guarantee the qualified items; Sumring items are certified by EN, UL, CE and ROHS.

Product market

SUMRING has 70% regular clients whom specialized in fire alarm & security area. The products are widely exported to Europe, North America, Africa, Middle East, and Asia. With customers over 40 countries.

Win-win cooperation

Inquiry us and enjoy a safe and secure life with SUMRING!



WHY CHOOSE US

PRODUCTION

10 times test procedures (28 hours) in production



CLIENT

40% regular client more than 10 years



EFFICIENCY

Short Leadtime: 2 days for sample 5 days for order



CERTIFY

Comply to EN54 EN14604 CE and ROHS



EXPERIENCES

5 senior engineers with 10 years experiences; Release 2 new products in 6 month



SERVICES

2 years warranty; Response inquiry in 24 hours



CATALOGUE

P **01** Enterprise introduction
Win-win cooperation

DETECTOR **03** P
CO GAS FIRE DETECTOR

P **09** FIRE ALARM SYSTEM
fire alarm system

SECURITY ACCESSORIES **12** P
Anti-theft alarm system



SR-918DSY

Technical parameters:

Sensor life: 5 years
Power Supply: AC90-240V
Alarm sound: Alarm sound: >85dB /1 meter
Product specifications:
Length:Product specifications: 121*79*40 mm

Detection gas: GAS+CO
Working temperature: -10°C-55°C



High sensitive

High quality sensor, more accurate detection, quick alarm in a short time, more secure guard your family



Dual power supply

using main power supply and 9v rechargeable battery as back up, convenient for anyunstable power supply scene.



Human voice broadcast

80dB high-pitched alarm, voice broadcast, more accurately know the alarm reason



Control valve

automatic linkage control solenoid valve closed, effectively avoid gas leakage caused by explosion and fire



SR-902-2Y

Technical parameters:

Product name: household combustible gas alarm

Detection gas: natural gas, liquefied gas, and pipeline gas.

Operating voltage: AC 90-240V

Alarm concentration: 8%LEL(+/-3%)

Working humidity: ≤95RH

Dimensions: 100*60*30mm

Alarm sound pressure: ≥90dB

Operating temperature: -10°C~+50°C

Working pressure range: 800hpa~1100hpa

Standard: CE, ROHS, EN50194



High tone alarm

Within 3m, the alarm sound is greater than 90dB, and the light flashes and the concentration is displayed (with LCD display)



LED display

The LCD screen displays real-time concentration.



Smart design

100*60*30mm lower down the shipping cost



Fault self-test

Press the "Test" button at any time to check the status of detector's alarm sound and light signal.



coal



Gas water heater

SR-907

Technical parameters:

Product Name: Carbon Monoxide Alarm

Detection gas: CO

Sensor life: 5 years

Static current: <10uA

Alarm current: <100mA

Working temperature: -10~50°C

Product size: diameter:100mm* thickness:41mm

Sensor: Electrochemical Carbon Monoxide Sensor

Carbon monoxide gas detection concentration: 000~999PPM

Alarm indication: LCD display, sound and light tips

Power supply: 3*1.5V AA Batteries, DC4.5V

Alarm sound: more than 85dB/meter

Working humidity: relative humidity 10%-95%

Battery display: low battery alarm



Hush Button

When the alarm occurs, handle the alarm, one key to cancel the alarm sound



Long lifetime sensor

The service life of the sensor is up to 5 years. Can OEM as 10 years lifespan.



MCU intelligent chip

Newly upgraded MCU with 48 pin IC chip, faster response and lower energy consumption



End-of-life remind

The life indicator(yellow) is always on, and the LCD displays LF (life)Remind 15 days before the end of service life



fireplace



coal



Carbon fire



smoke & CO

SR-822THS

Technical parameters:

Product name: combination smoke&carbon monoxide detector
 Operating voltage: 3*1.5V AA replaceable battery (3 AA 1.5V)
 Alarm sound pressure: ≥90dB Sensor life: 3 years
 Operating temperature: -10°C~+50°C Acquisition method: Natural diffusion
 Alarm setting value: Smoke is 0.3dB/M
 Installation: Wall or Ceiling mounted Package Size: 107*37mm



High sensitive

Second generation imported chips
 High sensitivity detection



Dual detection

fire smoke and CO, At the same time, more comprehensive protection of home safety



High tone alarm

Within 3m, the alarm sound is greater than 90DB, and the light flashes and the concentration is displayed (with LCD display)



Fault self-test

Press the "Test" button at any time to check the status of detector's alarm sound and light signal.

Combustible gas detector



SR-908

Series



SR-918-2

Series



SR-912

Series



SR-901

Series



SR-902



SR-903



SR-915

WIFI



SR-903-2

12V,Network



SR-910

12V,Network

Solenoid valve



SR-510



SR-510(S)



SR-510(D)



SR-511

Carbon monoxide detector



SR-921

with hush button



SR-909-2

Smart design



SR-907-2

Combined detector



CO+SMOKE

SR-821THS



CO+SMOKE

SR-823THS



SMOKE+HEAT

SR-820DHS

10 Years Standalone smoke alarm



SR-825PHS



SR-826PHS



SR-808

Standalone smoke alarm



SR-803



SR-803-2



SR-803-3



SR-807

WIFI Smoke alarm



SR-803-4W

CO2 detector



SR-909-CO2-B



SR-909-CO2-D

Water leakage detector



SR-W03BHS

Standalone/Network



SR-W04I

Standalone/Network



SR-WS02W

WIFI

Motion detector



SR-601W

110



SR-603W

360



SR-605DTP

Pet immunity

Motion light switch



SR-612I



SR-612O



SR-612B



SR-A08-PS

Product overview:

This product is made of imported PC material and is cast in one time. The whole body is transparent and the inner and outer walls are smooth, Beautiful and generous, high temperature resistance, high strength, impact resistance, good water drainage, dust prevention and corrosion resistance, This product is applicable to all kinds of industrial and mining environments, buttons and switches of high and low voltage distribution cabinets.



Splash prevention

resistance, good water drainage, dust prevention and corrosion resistance

DCW

Dust prevention

24 hours real-time detection
Ensure the safety of family life and property



Audible alarm

When closing the protective cover, if someone opens it, it will make a sound



thermostability

Adopt fireproof transparent plastic, which can be used in harsh environment



2/4 wire Smoke detector



SR-801



SR-802



SR-816



SR-813

2/4 wire Heat detector



SR-501



SR-504



SR-503



SR-812

Smoke+Heat
combined

Fire bell



SR-A91

12/24V



SR-A92

12/24/110-220V



SR-A93

12/24V



BACK BOX

For outdoor

Fire strobe Siren/lamp



SR-107

Outdoor



SR-111

Outdoor



SR-108

12/24/220V



SR-A82



SR-A81



SR-A77



SR-A79E



SR-A08

Manual call point

Remote indicator/ Repeater



SR-A02



SR-A05



SR-A77-F



SR-P01-R



rain



outdoor

SR-M55L

Product overview:

Name: Magnetic Door With Bracket

Case Material: Zinc Alloy

Color: grey

Gap: 50-70 mm

Current / Voltage / Power: 0.5A/100V/10W

Output: NC/NO/COM

Installation: buried or surface mounting

Connection: 22#wire, 550MM, with 380mm stainless steel protective tube



Splash prevention

Good waterproof, dustproof and corrosion resistance



Sensitive

High-quality line motherboard, current protection and sensitive response



Magnetic induction

can OEM distance with strong magnet.



Simple installation

Easy to use without complicated installation

SR-B001R

Wireless SOS alarm



SR-B002R



RF WIRELESS

**SR-WG30 GSM & WIFI
alarm system**

WIFI&GSM

SR-B002R & SR-B001R

Product overview:

Brand name: Wireless SOS alarm
Color: White
Sound: 80-90db
Weight: 120g

Network: Wireless frequency 433HZ
Battery: AAA1.5V
the tinkle of bells: 50 ringtones
Size: 80*80*65mm



low power consumption

Low-power design, can be used for long-term standby



transmission distance 300 Meters

The open wireless transmission distance is up to 300M,



Audible alarm

The volume is adjustable in 4 levels from 0db to 90db, so this pager can be heard even with loud background noise.



52 ringtones

The elderly call button is located 100m from the open area, and there are 52 kinds of ringtones to choose from.



SR-M31



SR-M32



SR-M37



SR-M38



SR-M58



SR-M59



SR-M60



SR-M33A/33B



SR-M38C



SR-M39



SR-M40



SR-M44A



SR-M34A/34B



SR-M35



SR-M36



SR-M41A



SR-M51



SR-M52



SR-M55A/M55B



SR-M57



SR-M41C



Horn



SR-A75



SR-A76
Sound Adjustable



SR-A76-30
30W



SR-A76-20
20W

RF Button



SR-A76-15
15W



SR-B002R-P



SR-B001R-P



SR-M304

Stainless Door loop



SR-P201



SR-P301



SR-P401



SR-P402

Wired Button



SR-A65



SR-A64



SR-A71



SR-A69A

Detector Shell




SR-A68-B
Black/Goden/White



SR-GHZ-A



SR-GJA-A



SR-GRT-B

ENJOY A SAFE AND SECURE LIFE WITH SUMRING